

## **C** € DECLARATION OF PERFORMANCE

Ref: TF CLAD-04

| 1. Unique identification code of the product-type:  | SertiWOOD® Thermowood® PNSY  |
|---|--|
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):   | PNSY Pinus Sylvestris European / Scandanavian Redwood Pine   |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:   | Solid wood cladding, 9mm minimum thickness for interior use on walls and ceilings and 16/18mm minimum thickness for external use in accordance with EN14915                          |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  | Timber Focus Ltd<br>3000 Aviator Way, Manchester, M22 5TG  |
| 5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  | AVCP 4   |
| In case of the declaration of performance concerning a construction product covered by a harmonised standard:   | The manufacturer has taken responsibility for initial type testing and implementation of factory production control, in accordance with AVCP level 4.                                |
| Harmonised technical specification - BSEN 14915 Solid wood panelling and cladding; characteristics, evaluation of conformity and marking  |  |
| 7. Essential characteristics  | Performance  |
| Density: Reaction to Fire: Formaldehyde class: Content Of Pentachlorophenol Water vapour permeability: Release of other dangerous substances: Sound absorption coefficient: Thermal Conductivity: Resistance to fixings: Durability: BS EN 350-2:1994 | 450kg/m³ D-s2, d0 E1 ≤ 5 x 10 <sup>-6</sup> " Wet: 20 Dry: 50 NPD (250 − 500Hz): 0.10 (1000-2000Hz): 0.30 0.12 W/(mK) Predrilling advisable Natural durability Class 2 BS EN 335 UC3 |
| 8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.  This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.         | Andrew Goto Head of Sales Manchester UK 01-07-2018 (place and date of issue)   |

BS 8605-2014 BS 1186-3 BS EN 942 WPA Commodity Specification C6







