

FA6615 10 YEAR SMOKE ALARM - Optical, 5 Year Replaceable Battery

| | |
|---------------------|--|
| Sensor type | Optical |
| Battery type | 2 x AA Alkaline Replaceable Batteries (Included) |



- Battery powered optical smoke alarm
- Reduces nuisance cooking alarms
- Large central test button
- Sleep Easy - silence the low battery chirp for 8 hours
- Operating Light (RED) - flashes approximately every 40 seconds confirming alarm is powered
- Low Battery Warning - 'beeps' approximately every 40 seconds when the battery needs replacing
- Loud 85 Decibel Piezo Electric Alarm
- Suitable for leisure accommodation vehicles (LAV)
- Easy Installation - fixings supplied
- Quiet test function supports discreet testing at a lower volume when compared to standard alarms



22
1116
EN 14604:2005+AC:2008
Smoke Alarm Devices
FSTDOP21006



22
0832
EN 14604:2005+AC:2008
Smoke Alarm Devices
FSTDOP21007

Technical Specification

| | | |
|--------------------------------------|--|--|
| Dimensions | 118.1mm (diameter) x 31.5mm (depth) | |
| Battery | 2 x AA Alkaline Replaceable Batteries (Included) | |
| Sensor Technology | Optical | |
| Alarm sound level | 85dB(A) at 3m (minimum) | |
| Installation positions | Wall/Ceiling | |
| Operating temperature | +4°C to +38°C | |
| Operating humidity | Up to 90% RH (non condensing) | |
| Storage temperature | -20°C to +60°C | |
| Storage humidity | Up to 93% RH (non condensing) | |
| Warranty | 5 Years | |
| Certified to | EN 14604:2005+AC:2008 | |
| Weight | 185g | |
| Leisure Accomodation Vehicles | Yes | |