HOMEBASE SIENNA 6 SEATER DINING SET -TABLE

INSTRUCTION MANUAL



SAFETY & CARE ADVICE

Please read these instructions fully before starting assembly.

- Aluminium is soft metal and over tightening may strip thread or break the part.
- Do not use power tools however you will require a spanner and flat head screw driver to assemble product.
- Please allow 30 minutes for assembly.
- Although assembly only requires 1 person it is advised that a second person be present to help turn the table over and into position when fully assembled.

COMPONENTS- PARTS & FITTINGS

Please check you have all the components and fittings listed. If you find any missing or damaged parts, please contact our customer services team on 0333 003 7084 between 09:00 & 18:00, or use the contact form on our website www.homebase.co.uk.

NOTE: The quantities below are the correct amount to complete the assembly. In some cases, more fittings may be supplied than required.

Component's				Fixings			
Parts List	Parts Picture	Description	Qty	Parts list	Parts Picture	Description	Qty
А		Table Top	x1	D	(<u>((((()))))</u> (M8*40)	Bolt	x4
				E	(M8)	Flat Washer	x12
В	\Box	Centre Square	x2	F	О (м8)	Lock Washer	x12
				G	(M8)	Nut	x4
С		Table leg	x4	Н	(M8)	Nut Cap	x4
				I	(M8*40)	Bolt	×8
				k		Allen Key	x1
				L	-	Screw in feet	x4

ASSEMBLY INSTRUCTIONS

Step 1:

Loosely attach the centre square (B) to the legs (C) with bolts (I) flat washers (E), lock washers (F) and nuts (G) using the allen key (K). Do not tighten the bolts at this stage.

Step 2:

Turn the table top (A) upside down on a soft clean surface.

Using flat head screw driver, screw the bolts (D) into the table top (Refer to diagram). Do not tighten the bolts at this stage.

Step 3:

Attach the 4 legs (C) to the table top at the points where the bolts (D) have been placed. Then slide flat washers (E), lock washers (F), and nuts (G) on to the bolt. Do not tighten the nuts at this stage.

Tighten all the bolts and nuts one by one, being careful not to over tighten any, as this will cause the thread to become damaged.

Tighten all the bolts and nuts then cover nut cap (H).

Step 4:

Turn the table onto its legs and use the screw in feet (L) to level the table.









