



tesa[®] extra Power Universal

Product Information



BNR 56338, 56348, 56384, 56385, 56386, 56388, 56389, 56396, 56488, 56490

Product Description

tesa[®] extra Power Universal is a versatile duct tape with extra bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------|
| • Backing material | PE-film with PET-filament | • Total thickness | 215 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|--------------------------|------|
| • Tensile strength | 100 N/cm | • Solvent free | yes |
| • Adhesive strength | High adhesion | • Tear resistance | yes |
| • Ageing resistance (UV) | yes | • Temperature resistance | yes |
| • Hand tearability | yes | • Tensibility | 19 % |
| • Humidity resistance | yes | • UV resistant | yes |
| • Oil and grease resistance | yes | • Water resistance | yes |
| • Ozone resistance | yes | • Waterproof | yes |
| • Residue free removal | no | • Writable | no |



tesa[®] extra Power Universal

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=56338>