



Preheat plates and cups, so that dishes stay hot longer. Keep warm, for keeping cooked dishes warm.

- $\sqrt{\,}$ Slow Cook Programme For tender meats, poultry, and vegetables packed with flavour and vitamins.
- $\sqrt{\,}$ Installation with compact appliance combine your drawer with any 45 cm appliance

Optional accessories

Z11SZ60G0 SeamlessCombination 45 + 14cm

Features

Technical Data

Construction type: Built-in Color / Material Front: Graphite Maximum number of plates: 12 Maximum number of espresso cups: 64 Dimensions: 140 x 594 x 518 mm

Dimensions of the packed product (HxWxD) : $250 \times 660 \times 700\,$ mm Min. required niche size for installation (HxWxD) : $140 \times 560 \times 550\,$

mm

EAN code: 4242004265719 Fuse protection: 10 A Voltage: 220-240 V Frequency: 50-60 Hz Plug type: GB plug





N 70, Built-in warming drawer, 60 x 14 cm, Graphite-Grey N24HA11G1B

Feature:

- Multifunctional warming drawer with the heating functions: Low temperature cooking, Keep warm, plate warming, cup warming
- Can accommodate up to:
 - -12plates
 - -64 espresso cups

Design

- Graphite-Grey Edition
- Touch Control illuminated
- Touch key operation

Programmes/functions

- User-friendly electronics: extremely easy and comfortable operation
- Favourites button manage via Home Connect app
- Temperature control in 4 levels: ca. 30°C 80°C (glass surface temperature)
- Push-Pull opening mechanism
- Easy to clean toughened glass heating plate

Performance/technical information


- Nominal voltage: 220 240 V
- Total connected load electric: 0.82 KW
- Cavity volume: 20 l
- Loading up to 25 kg
- \bullet Appliance dimension (hxwxd): 140 mm x 594 mm x 518 mm
- Niche dimension (hxwxd): 140 mm x 560 mm 568 mm x 550 mm
- In case of installation under the worktop, installation accessory spare part no. 9001698838 is needed.
- Please refer to the dimensions provided in the installation manual








Dimensioned drawings





A: 7.5 mm

Compact ovens with appliance height of 455 mm can be installed above the warming drawer without an intermediate floor